


GIBELA

2025-05-08

GIBELA

CONTROLLED COPY

PRASA PROJECT



# SELF INSPECTION SHEET

**CONFIDENTIAL INFORMATION**

This document and the information contemplated therein have to be considered as Confidential Information pursuant to the provisions of Clause 25 of the MSA, and treated as such.

**APPLICATION REFERENCE**

MOUNTING	DESCRIPTION	STATION	CAR TYPE						WORK INSTRUCTION	SAFETY ? 	
			TC1	M4	M1	M2	M3	TC2			
<input type="checkbox"/>	DTR3-PROCE-14	LEVELLING, WEIGHTING AND BALANCING M CAR	FT1140		1	1	1	1		PRA.FT1140.04	YES
<input type="checkbox"/>	DTR3-PROCE-14	LEVELLING, WEIGHTING AND BALANCING TC CAR	FT1140	1					1	PRA.FT1140.05	YES
<input type="checkbox"/>	DTR3-PROCE-17	LEVELLING, WEIGHTING AND BALANCING TC CAR	FT1140	1	1	1	1	1	1	PRA.FT1140.05	YES
<input type="checkbox"/>	DTR3-PROCE-17	LEVELLING, WEIGHTING AND BALANCING TC CAR	FT1140	1	1	1	1	1	1	PRA.FT1140.05	YES
<input type="checkbox"/>											
<input type="checkbox"/>											
<input type="checkbox"/>											

REV	DATE	MODIFICATION CONTENT	RESPONSIBLE	NAME	DATE
7	2/11/2020	UPDATE OF AIR TIGHTNESS TEST TIME FROM 4 MIN TO 5 MIN. ADD PANTOGRAPH AIR TIGHTNESS.	APPROVER	GIVEN SILOWA	2/11/2020
			CHECKER	SIMON MOKOENA	2/11/2020
			COMPILER	COMFORT MALATJI	2/11/2020
8	9/13/2021	ADDING GAUGE MEASUREMENT CHECK ON THE SI.	APPROVER	MAKOFANE LUCY	9/13/2021
			CHECKER	RATAU EDISON	9/13/2021
			COMPILER	TSAKANI KHOSA	9/13/2021
9	5/31/2022	pressure valve (APV) Isolation	APPROVER	MAKHURUPETJI THABANG	5/31/2022
			CHECKER	HAZEL MGIBA	5/31/2022
			COMPILER	RATAU EDISON	5/31/2021

TUE	CAR	OPERATOR NAME	DATE	SELF INSPECTION NUMBER	PAGES
TS 221	M3	P. SEISA	08/05/24	SI.FT1140.52	01/08





# SELF INSPECTION INDUSTRIAL QUALITY

Rev:09

Date:

5/31/2022

Project:  
PRASA

SI.FT1140.52

Car:

NCR:

Work Station

FT1140



Safety Related


## I - Document and Instrument Control

### I.1 - Documents control



Document	T01	M1	M2	M3	M4	T02	Revision	Name	OK	TRK	Signature/Date
PRA.FT1140.04											
PRA.FT1140.05				K					✓		08/05/24
PRA.FT1140.05											


### I.2 - Instruments Control - Monitoring and Measuring Instrument Control (Used for all instrument with calibration needed)

Instruments description	Serial number	Calibration or Verification Validation Date	OK	TRK	Signature/Date
Measuring tape	G1B7A 0276	26/10/23-26/10/24	✓		
Venier Calliper	G1B4R 0056	06/06/23-06/06/24	✓		
Torque Wrench 35 N.m	D0511023	19/12/23-19/12/24	✓		08/05/24
Torque Wrench 150 N.m	D08622009	19/12/23-19/12/24	✓		
Torque Wrench 320 N.m	A9650027	21/12/23-21/12/24	✓		



**II - Self Inspection - Items to Check**

B.1 - Items to Check															
Item	Picture/Sketch	Description	Criteria/Record	OK	NOK	Status	Signature/Date								
01		Ensure that the average pressure valve (APV) is isolated by capping the two In-A pipes at the fittings installing the blanking flang on the pipes highlighted		✓			 08/08/24								
02		Check underframe pipe system Air tightness. Test performance according to WI FRA.FT1130.15.	The test was performed and no leak was observed. Initial pressure (PI) <u>10.00</u> bar Final pressure (FP) <u>9.98</u> bar FP - IP <u>0.02</u> bar APPROVAL CRITERIA: After 5 minutes the pressure cannot drops more than 0.2 bar	✓			 08/08/24								
03		Movement performed at least 50m to shudder the car. And position on the leveled load cell, with wheels on the center.		✓			 08/08/24								
04		Measurement inspection was done with car on condition AWD and the rail leveled. (The load cell's system must be leveled and calibrated)	Calibration Validation Date <u>19.12.24</u>	✓			 08/08/24								
05		In case of the equipments not installed, equivalent weight of the item should be added in the same place to simulate the equipment. (Any simulated weight, add on pending list)	<table border="1" style="width: 100%; border-collapse: collapse; font-size: 8px;"> <thead> <tr> <th style="width: 80%;">EQUIPMENT DESCRIPTION</th> <th style="width: 20%;">WEIGHT (kg)</th> </tr> </thead> <tbody> <tr> <td><u>BANCWAYS</u></td> <td style="text-align: center;"><u>360</u></td> </tr> <tr> <td> </td> <td> </td> </tr> <tr> <td> </td> <td> </td> </tr> </tbody> </table>	EQUIPMENT DESCRIPTION	WEIGHT (kg)	<u>BANCWAYS</u>	<u>360</u>					✓			 08/08/24
EQUIPMENT DESCRIPTION	WEIGHT (kg)														
<u>BANCWAYS</u>	<u>360</u>														
06		The pressure difference between air spring on each bogie when raise the pressure was maintained < 0.3 bar.		✓			 08/08/24								
07		Measurement recorded with empty suspension and loaded are on conformity with tolerances of the project.		✓			 08/08/24								
08		All leveling measurements are according to the reference. (Values out of reference must be recorded on "Description of defects")		✓			 08/08/24								

  
 2025-05-08  
**CONTROLLED COPY**



# SELF INSPECTION INDUSTRIAL QUALITY

Rev:09


Date:

5/31/2022

Projet:  
PRASA

SI.FT1140.52

Item	Picture/Sketch	Description	Criteria/Record	OK	NO	Other	Signature/Date
09		Check that the leveling rods are torqued and have torque marker.		✓			 08/05/24
10		The difference of weight between the left and right wheels of each axis, must be ≤ 4%. (Verify on the T&C equipment if all arrows are in green).		✓			 08/05/24
11		Remove the car, move back onto the load cells and repeat the step 09. Confirm if both are in the tolerance of ≤ 4%.		✓			 08/05/24
12		1 - Record shims thickness used on rod 2 - All screws were torqued and have torque marker.	THICKNESS (mm) I II III IV	✓			 08/05/24
13		Pivot fixation	1- M20 x 90 screws with application of torque according to PRA FT1140.04 / 05	✓			 08/05/24
14		FOR TC CARS F= Height of the center of Automatic coupler F = 895mm (+5 / -10mm) (Using levelled rail)	TC CAB #1= _____ mm				N/A
15		FOR TC CARS Height of Eurobase Antenna = 205mm(+/-10mm) (Using levelled rail)	TC CAB #1= _____ mm				N/A
16		Check pantograph piping air tightness. Test performance according to WI PRA FT1140.17.	The test was performed and no leak was observed. -Roof piping connection fittings. -Room piping connection fittings(Roof arch and door trimming)				N/A
17		Pantograph does not come in contact with the higher height gauge when passing through.	No Contact with Pantograph and Gauge -GO Contact with Pantograph and Gauge - NO GO				N/A
18		Car does not come into contact with the gauge.	No Contact with Car and Gauge -GO Contact with Car and Gauge - NO GO	✓			 08/05/24





# SELF INSPECTION INDUSTRIAL QUALITY

Rev:09

Date:

5/31/2022

Proj:  
PRASA

SI.FT1140.52

DRAFT TO MEASUREMENTS DURING LEVELLING (ALL UNITS MUST BE IN mm/bar/kg)														
DESCRIPTION	TOLERANCE	LEFT SIDE						RIGHT SIDE						
		6	5	4	3	2	1	1	2	3	4	5	6	
AIR SPRING HEIGHT (EMPTY)	N/A	A'ii	/	/	/	/	/	/	/	/	/	/	/	A'i
AIR SPRING HEIGHT (FULL)	min 254 max 261	Aii	/	/	256	254	249	243	/	253	257	256	257	Ai
FLOOR COVERING HEIGHT	min 1096 max 1116	Eii	/	/	1111	1109	1098	1096	/	1105	1110	1110	1110	Ei
AIR SPRING PRESSURE	± 0.3 (Ci - Cj)	Cii	/	/	2.74	2.65	2.46	1.68	/	2.71	2.91	2.79	2.72	Ci
PRIMARY SUSPENSION	SEE TABLE (ONLY REF)	D3	/	/	/	/	/	/	/	/	/	/	/	D1
PRIMARY SUSPENSION	SEE TABLE (ONLY REF)	D4	/	/	/	/	/	/	/	/	/	/	/	D2
PIVOT VERTICAL GAP	min 25 max 32	Kii	/	/	/	/	/	/	/	/	/	/	/	Ki
PIVOT LATERAL STOP GAPS DIFFERENCE	± 4 (Ji - Jj)	Jii	/	/	/	/	/	/	/	/	/	/	/	Ji
QTY OF TURNS OF LEVELLING ROD	N/A	Xii	/	/	/	/	29	28	/	1	A	/	/	Xi
SHIMS OF ANTI-ROLL BAR	N/A	Yii	/	/	/	/	/	/	/	/	/	/	/	Yi
AIR SPRING HEIGHT (EMPTY)	N/A	A'iii	/	/	/	/	/	/	/	/	/	/	/	A'iv
AIR SPRING HEIGHT (FULL)	min 254 max 261	Aiii	/	/	256	256	255	252	/	251	255	255	256	Aiv
FLOOR COVERING HEIGHT	min 1096 max 1116	Eiii	/	/	1109	1109	1109	1105	/	1103	1107	1107	1107	Eiv
AIR SPRING PRESSURE	± 0.3 (Cv - Cv)	Ciii	/	/	2.73	2.81	2.99	2.91	/	2.37	2.46	2.63	2.75	Cv
PRIMARY SUSPENSION	SEE TABLE (ONLY REF)	D5	/	/	/	/	/	/	/	/	/	/	/	D7
PRIMARY SUSPENSION	SEE TABLE (ONLY REF)	D6	/	/	/	/	/	/	/	/	/	/	/	D8
PIVOT VERTICAL GAP	min 25 max 32	Kiii	/	/	/	/	/	/	/	/	/	/	/	Kiv
PIVOT LATERAL STOP GAPS DIFFERENCE	± 4 (Jv - Jv)	Jiii	/	/	/	/	/	/	/	/	/	/	/	Jiv
QTY OF TURNS OF LEVELLING ROD	N/A	Xiii	/	/	/	/	1	A	/	1	A	/	/	Xiv
SHIMS OF ANTI-ROLL BAR	N/A	Yiii	/	/	/	/	/	/	/	/	/	/	/	Yiv


  

COMPARE EACH TENTATIVE WITH THE TOLERANCE AND IDENTIFY EACH MEASURE AS BELOW			BOGIE ORIENTATION	
GOOD	LOWER	HIGHER		
✓	↓	↑		
WEIGHT COMPENSATION				
EQUIPMENT				
WEIGHT				
EQUIPMENT				
WEIGHT				
SECONDARY MEASUREMENTS (ONLY TC CARS)				
AUTOMATIC COUPLER HEIGHT				
ANTENNA HEIGHT				

BOGIE END#1

BOGIE END#2





# SELF INSPECTION INDUSTRIAL QUALITY

Rev:09

Date:

5/31/2022

Proj:  
PRASA

SI.FT1140.52

## DRAFT TO MEASUREMENTS DURING LEVELLING (ALL UNITS MUST BE IN mm/bar/kg)

DESCRIPTION	TOLERANCE	LEFT SIDE						RIGHT SIDE						
		6	5	4	3	2	1	1	2	3	4	5	6	
AIR SPRING HEIGHT (EMPTY)	N/A	A'ii	/	/	/	/	/	/	/	/	/	/	/	A'i
AIR SPRING HEIGHT (FULL)	min 254 max 261	A'ii	/	/	/	/	/	/	/	/	/	/	/	A'i
FLOOR COVERING HEIGHT	min 1096 max 1116	Eii	/	/	/	/	/	/	/	/	/	/	/	Ei
AIR SPRING PRESSURE	≤ 0.3 (Ci - C)	Cii	/	/	/	/	/	/	/	/	/	/	/	Ci
PRIMARY SUSPENSION	SEE TABLE (ONLY REF)	D3	/	/	/	/	/	/	/	/	/	/	/	D1
PRIMARY SUSPENSION	SEE TABLE (ONLY REF)	D4	/	/	/	/	/	/	/	/	/	/	/	D2
PIVOT VERTICAL GAP	min 25 max 32	Kii	/	/	/	/	/	/	/	/	/	/	/	Ki
PIVOT LATERAL STOP GAPS DIFFERENCE	≤ 4 (Ji - Ji)	Jii	/	/	/	/	/	/	/	/	/	/	/	Ji
QTY OF TURNS OF LEVELLING ROD	N/A	Xii	/	/	/	/	/	/	/	/	/	/	/	Xi
SHIMS OF ANTI-ROLL BAR	N/A	Yii	/	/	/	/	/	/	/	/	/	/	/	Yi
DESCRIPTION	TOLERANCE	6	5	4	3	2	1	1	2	3	4	5	6	
AIR SPRING HEIGHT (EMPTY)	N/A	A'iii	/	/	/	/	/	/	/	/	/	/	/	A'iv
AIR SPRING HEIGHT (FULL)	min 254 max 261	A'iii	/	/	/	/	/	/	/	/	/	/	/	A'iv
FLOOR COVERING HEIGHT	min 1096 max 1116	Eiii	/	/	/	/	/	/	/	/	/	/	/	E'iv
AIR SPRING PRESSURE	≤ 0.3 (Civ - Ci)	Ciii	/	/	/	/	/	/	/	/	/	/	/	C'iv
PRIMARY SUSPENSION	SEE TABLE (ONLY REF)	D5	/	/	/	/	/	/	/	/	/	/	/	D7
PRIMARY SUSPENSION	SEE TABLE (ONLY REF)	D6	/	/	/	/	/	/	/	/	/	/	/	D8
PIVOT VERTICAL GAP	min 25 max 32	Kiii	/	/	/	/	/	/	/	/	/	/	/	K'iv
PIVOT LATERAL STOP GAPS DIFFERENCE	≤ 4 (J'iv - Ji)	J'iii	/	/	/	/	/	/	/	/	/	/	/	J'iv
QTY OF TURNS OF LEVELLING ROD	N/A	Xiii	/	/	/	/	/	/	/	/	/	/	/	X'iv
SHIMS OF ANTI-ROLL BAR	N/A	Yiii	/	/	/	/	/	/	/	/	/	/	/	Y'iv

COMPARE EACH TENTATIVE WITH THE TOLERANCE AND IDENTIFY EACH MEASURE AS BELOW

GOOD	LOWER	HIGHER
✓	↓	↑

WEIGHT COMPENSATION

EQUIPMENT	
WEIGHT	
EQUIPMENT	
WEIGHT	

SECONDARY MEASUREMENTS (ONLY TO CARS)

AUTOMATIC COUPLER HEIGHT	
ANTENNA HEIGHT	





Table 1 - Reference Values and Measurement Tolerances for the Car Levelling.

ITEM	THEORETICAL VALUES											
	T1 CAR		M4 CAR		M1 CAR		M2 CAR		M3 CAR		T2 CAR	
	TBtest	TBIRK	MB1	MB2	MB1	MB2	MB1	MB2	MB1	MB2	TBIRK	TBtest
Pivot lateral stop gap difference [mm]	Fig. 4	≤4	≤4	≤4	≤4	≤4	≤4	≤4	≤4	≤4	≤4	≤4
Air Spring height [mm]	Fig. 5	255 <sup>+4</sup> <sub>-4</sub>										
Air spring pressure at AWO [Bar]	Fig. 5	3,76 (Ref.)	2,82 (Ref.)	2,83 (Ref.)	2,91 (Ref.)	3,07 (Ref.)	2,85 (Ref.)	2,83 (Ref.)	2,83 (Ref.)	2,87 (Ref.)	2,83 (Ref.)	3,76 (Ref.)
Primary Suspension gaps [mm]	C <sub>1</sub> (1+10)	0,3 Máx.										
	C <sub>1</sub> -C <sub>2</sub>											
	C <sub>3</sub> -C <sub>4</sub>											
	D <sub>1</sub> ; D <sub>2</sub>											
Carbody Floor height [mm]	Fig. 6	35 <sup>+2</sup> <sub>-4</sub>										
	D <sub>1</sub> ; D <sub>2</sub>											
	D <sub>3</sub> ; D <sub>4</sub>											
Bumper height [mm]	Fig. 7	1106 <sup>+10</sup> <sub>-10</sub>										
	N <sub>1</sub> (1+10)	850 <sup>+2</sup> <sub>-2</sub>										
Coupling End height [mm]	Fig. 8	895 (Ref.)	760 (Ref.)	895 (Ref.)	895 (Ref.)							
	Fig. 9	760 (Ref.)										
Pivot Vertical gap [mm]	Fig. 10	30 <sup>+3</sup> <sub>-5</sub>										
	K <sub>1</sub>											

2025 - 05 - 0 8  
**CONTROLLED COPY**



# SELF INSPECTION INDUSTRIAL QUALITY

Rev:09

Date:

5/31/2022

Projeto:  
PRASA

SI.FT1140.52

Leveling report from Production (Final measurements after Levelling and Weighing fine)

References for secondary suspension empty  
A'n Air spring height empty


References for secondary suspension full  
An Air spring height  
Bn Difference between measurement A'n and An  
En Floor covering height  
Cn Air spring pressure  
Dn Primary suspension  
Kn Pivot Vertical gap  
Jn Pivot Lateral stop gaps difference

Item	Reference [mm]	END#1		END#2	
		Right Side	Left Side	Left Side	Right Side
A'n	N/A	A'i 242	A'ii 242	A'iii 241	A'iv 242
An	254 to 261	Au 257	Aii 256	Aui 256	Av 256
Bn = An - A'n	N/A	Bi	Bii	Biii	Biv
En	1106 ±10 mm	Ei 1110	Eii 1111	Eiii 1109	Eiv 1107
Item	Reference [bar]	END#1		END#2	
Cn	Table 02 (*)	Ci 2.72	Cii 2.74	Ciii 2.73	Civ 2.73
Cn - Cn	Diference ≤ 0,3	Ci - Cii		Ciii - Civ	
Gauge serial number	N/A			91805873	91805873
Item	Reference [mm]	END#1		END#2	
Dn	Table 01 (*)	D1 46.39	D3 46.29	D5 46.16	D7 46.71
		D2 46.09	D4 46.48	D6 46.55	D8 45.93
Kn	25 to 45	Ki 38.01	Kii	Kiii 38.24	Kiv
Jn=J1-J2+1	Diference ≤ 4	Ji 24.67	Jii 26.18	Jiii 25.22	Jiv 25.67


(\*) Reference, only include values, isn't approval criteria.

Table 01 D Theoretical Values	TC1		M4		M1		M2		M3		TC2	
	Tbex	Tbin	Mb1	Mb1	Mb1	Mb2	Mb1	Mb1	Mb1	Tbin	Tbex	
D=	35 <sup>+12</sup> <sub>-5</sub>											

Table 02 C Theoretical Values	TC1		M4		M1		M2		M3		TC2	
	Tbex	Tbin	Mb1	Mb1	Mb1	Mb2	Mb1	Mb1	Mb1	Tbin	Tbex	
C=	3.76	2.82	2.87	2.83	3.02	2.91	3.07	2.85	2.83	2.87	2.83	3.76



Weighting report from Test and Commissioning (Final measurements after Levelling and Weighing fine)







Gibela Rail Transport Consortium RF (Pty)  
Ltd  
2 Shosholozza Avenue  
Dunmottar X7  
Ekurhuleni, 1590, South Africa  
Reception: +27 (0)10 600 0651

TRAIN SET 221 REF: GIB0000001672\_J0 PRASA WEIGHT BALANCE EN  
PC09 WEIGHING REPORT

M3	Balance across front and rear bogies	Front Bogie [Tons]		Rear Bogie [Tons]		Longitudinal Imbalance [%]		Criteria Longitudinal Imbalance ≤ 3%	
		Weight Measured [Tons]	Weight Predicted [Tons]	Weight Measured [Tons]	Weight Predicted [Tons]	Weight Difference [%]	Tolerance [%]	Criteria Min:Diff:Max	
	Weight Measured vs Predicted	35.74	35.90	17.87	17.87	0.45%	1.86%	PASS	PASS

Test Participants			
Name	Company	Department	Date
Thabo Musisi	GIBELA	EOC	08/06/2024

